

ACTIVE UV

TECHNICAL DATA SHEET

A PERFORMANCE BLANKET DESIGNED FOR UV PRINTING

MTech Active UV is a Quality Performance EPDM Surface Blanket Designed for printing with UV Inks.

Features:

1. E.P.D.M Micro-ground Surface.
2. Quick paper / board release.
3. Easy to wipe clean paper / board residue from the surface.
4. Excellent dot transfer.

OFFSET PRINTING RUBBER BLANKETS

Sheet-Fed



UV Ink



Packaging Printing



Commercial Printing



Technical Specifications:

- Colour	Black
- Thickness	1.95 mm $\pm$ 0.02mm
- Construction	3-ply Fabric
- Hardness	79 Shore A
- Surface Layer	Micro ground EPDM
- Roughness	0.86 μ m
- Elongation at 500N / 5cm	$\leq$ 0.90%

User Guidelines:



- Make sure that the blanket is cut in right angle.
- The blankets should be properly edge sealed.
- Check the blanket thickness from 3 different positions.
- Check the bar on the blanket thoroughly after the barring process.
- Mount the blanket as per OEM torque settings using a torque wrench.
- Preferably store the blankets flat (printing surface facing each other).

E.P.D.M Surface

Fabric Ply

Closed Cell Compressible Layer

Solvent Resistant Bottom Fabric



Corporate office:

MONEDA Technologies UG

Schraudolphstr. 13 b 80799 Munich, Germany

✉ business@monedatechnologies.com

MONEDA
TECHNOLOGIES

www.monedatechnologies.com

Disclaimer : In pursuit of constant product improvement, specifications are subject to change without prior notice. Rejections will be accepted subject to the millsapproval. All brand names and product names used here are trademarks belonging to their respective owners. The information provided in this document is to be used only as a guide. It does not imply any liability and shall not be binding upon the company.

© January 2024. Copyright reserved for design & content. Owner, Moneda Technologies UG .